

• Scanner Central Admin Software for fleet management

• Enhance productivity with Fujitsu service and support



fi-5530C2

Color Departmental Scanner

Performance Scanning for Demanding Users

The Fujitsu fi -5530C2 Color Departmental Scanner offers an incredible set of features in a compact package. Measuring only 11.5" by 16" by 9", the fi -5530C2 is an A3 scanner that handles a variety of document sizes. What's more, it scans at speeds up to 50 ppm / 100 ipm (landscape, 200 dpi), features dual color CCDs with true, 600-dpi resolution for capturing subtle details, and uses ultrasonic double-feed detection for reliable, automatic scanning. For greater ease-of-use, the fi -5530C2 includes a 100-page automatic document feeder (ADF) that handles documents ranging from 2.1" by 2.9" to 11" by 17" and Ultra SCSI and high-speed USB 2.0 interface for simplifi ed connectivity. And with the image enhancement capabilities provided with PaperStream IP and the advanced features included with new PaperStream Capture, the fi -5530C2 combines excellent handling performance with improved content control to deliver exceptional scanning results at an amazing value.

Fleet Management.

Scanner Central Admin provides IT departments an efficient way to manage medium to large scanner deployments. With remotely accessible fl eet information, IT departments can now allocate resources effectively based on scan volume, consumable wear, depreciation schedules and maintenance expiration.

On-site service helps maximize uptime

The fi -5530C2 scanner includes a 90-day, on-site, Limited Warranty. full details on the Limited Warranty and on all service programs, go to www.lmagingService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.

Model fi-5530C2 Technology Dual Color Charge coupled device (CCD) image sensor Optical Resolution G00 dpi G00 dpi S0 to 600dpi, 1200dpi² S0 to 600dpi. S0	
Optical Resolution 600 dpi Output Resolution 1 Monochrome Grayscale/Color 50 to 600dpi, 1200dpi² Halftone patterns 7 dither, 1 error diffusion, and 1 downloadable Grayscale 10 bit/1024 level (internal), 8 bit/256 level (output) Scanning Speeds ³ Simplex Duplex Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) ADF maximum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Sleep: 7.5	
Output Resolution 1 Monochrome Grayscale/Color 50 to 600dpi, 1200dpi² Halftone patterns 7 dither, 1 error diffusion, and 1 downloadable Grayscale 10 bit/1024 level (internal), 8 bit/256 level (output) Scanning Speeds 3 Duplex Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less,	
Halftone patterns 7 dither, 1 error diffusion, and 1 downloadable	
Grayscale 10 bit/1024 level (internal), 8 bit/256 level (output) Scanning Speeds ³ Output Simplex Duplex Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Power requirements (auto-switching) 100 − 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or Operating Environment Temperature 42° − 95°F (5°C − 35°C) Relative humidity 20% − 80% (non-condensing) Dimensions (WxDxH) 11.5 in. x 16.0 in. x 9.0 in.	
Scanning Speeds ³ Simplex Duplex Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-switching) 100 – 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Sleap: 7.5 W or le	
Output Simplex Duplex Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size AB [2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-witching) 100 – 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Sleaphy: 12 W or less, Sleep: 7.5 W or Relative humidity Operating Environment Temperature Relative humidity 20% – 80% (non-condensing) Dimensions (WxDxH) 11.5 in. x 16.0 in. x 9.0 in.	
Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-switching) Power consumption 100 – 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Sle	
Monochrome & Color @ 200dpi (A4, Portrait) 35 ppm 70 ipm Monochrome & Color @ 200dpi (A4, Landscape) 50 ppm 100 ipm Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-switching) Power consumption 100 – 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Sle	
Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-switching) 100 − 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or Operating Environment Temperature 42° − 95°F (5°C − 35°C) Relative humidity 20% − 80% (non-condensing) Dimensions (WxDxH) 11.5 in. x 16.0 in. x 9.0 in.	
Document feeding mode Automatic document feeder (ADF) ADF Capacity 100 Sheets (letter/A4, 20 lb.) Document size ADF minimum A8 (2.1 in. x 2.9 in.) ADF maximum A3 (11.7 in x 17 in) Interface USB 2.0, Ultra SCSI Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-switching) 100 − 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or Operating Environment Temperature 42° − 95°F (5°C − 35°C) Relative humidity 20% − 80% (non-condensing) Dimensions (WxDxH) 11.5 in. x 16.0 in. x 9.0 in.	
Document size	
A3 (11.7 in x 17 in) Interface	
ADF maximum	
Interface	
Scanner Memory 64MB Software Driver Support PaperStream IP (TWAIN/ISIS) Physical Specifications Power requirements (auto-witching) 100 − 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Sleep: 7.5 W or less, Standby: 12 M or less, Sleep: 7.5 W or less, Sleep:	
Software Driver Support PaperStream IP (TWAIN/ISIS)	
Physical Specifications Power requirements (auto-switching) 100 – 240 VAC, 50/60 Hz Power consumption 57 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Standby: 12 W or less, Sleep: 7.5 W or less, Slee	
Power requirements (auto-switching) 100 - 240 VAC, 50/60 Hz	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	
Operating Environment Temperature Relative humidity 42° - 95°F (5°C - 35°C) Dimensions (WxDxH) 20% - 80% (non-condensing) 11.5 in. x 16.0 in. x 9.0 in.	less
Dimensions (WxDxH) Relative humidity 20% – 80% (non-condensing) 11.5 in. x 16.0 in. x 9.0 in.	1000
Dimensions (WxDxH) 11.5 in. x 16.0 in. x 9.0 in.	
Environmental Compliance RoHS	
Reliability Specifications	
Limited Warranty 3 months on-site	
Service Options In-Warranty upgrades and Post-Warranty (Plus)	
Terms and conditions apply. A service contract must be executed to purchase all service programs noted in this document. On-Site: Basic (parts, labor and travel only) or ScanCare® (Preventative Maintenance, Consumables + Basic) Response Time Options: 4-hour or Next Business Day Unit Replacement: Advance Exchange; Unit Return: Depot Consumables: ScanAid™ Kits	
Options Imprinter	
OS Support Windows VSta® Windows Server® 2008 Windows 8 Fryer® 2008 Windows® 7 Windows® 8 Windows® 8 Windows Server® 2012	
Feature Ultrasonic double feed detection, selectable B&W background, long document scanning 4, hard card scanning, automatic de-ske automatic page size detection	ew,
Bundled Software (DVD Format) PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, E Recovery, PaperStream Capture, Scanner Central Admin Agent	rror
Part Number PA03334-B665	

- 1. Intel® Core™ i5 desktop processor 2.5 GHz or higher, 4 GB RAM is recommended.
- 2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600 dpi or higher).
- 3. Scanning speeds may vary due to the system environment used.
- 4. Up to 34 in.





















